




SC Connector



The SC connector features a 2.5mm Zirconia Ceramic ferrule and a push/pull coupling mechanism for a fast and reliable connection.

A range of pigtail, simplex and duplex SC connectors are manufactured including Standard and Premium Low Loss Grades which are suitable for various applications.

The SC connectors are available for single mode UPC with blue boots, for APC with green boots and for multimode PC with red or black boots suitable for 900µm, 2mm or 3mm cable diameters.

The SC/APC connector is available with a pre-angled ferrule designed for 8 degree angle polishing.

The SC connector housing and duplex clip are available in standard colors including blue (single mode), green (single mode APC) and beige (multimode).

FEATURES/BENEFITS

- Complies with IEC 61754-4 and TIA 604-3-B, FOCIS-3
- Low insertion loss and back reflection capability
- A push-pull coupling mechanism for easy insertion and consistent connection
- Connector housing and duplex clip available in different colors for easy identification
- Zirconia ceramic ferrule available in several performance grades
- RoHS materials, REACH SvHC compliant
- Individual parts packed in bulk package

APPLICATIONS

- Telecommunications networks
- CATV - Cable television
- Fiber-To-The-Home (FTTH)
- LAN, MAN and WAN application
- Data processing networks
- Premises distribution

SPECIFICATIONS

MECHANICAL PROPERTIES	CRITERIA	EFFECT	CONFORMANCE
Mating Durability	500 matings	<0.2 dB change	IEC 61300-2-2
Vibration	10-55Hz, 0.75 amplitude	<0.2 dB change	IEC 61300-2-1
Drop	Drop height 1m, 5 drops	<0.2 dB change	IEC 61300-2-12
Cable Retention	Magnitude 90N	<0.2 dB change	IEC 61300-2-4
Cable Torsion	1.5kg - 2.5kg for 2mm-3mm cable diameter	<0.2 dB change	IEC 61300-2-5
Operating Temperature	-25 to +70, 12 cycles	<0.2 dB change	IEC 61300-2-22
Cold	-25 for 96 hrs	<0.2 dB change	IEC 61300-2-17
Dry Heat	+70 for 96 hrs	<0.2 dB change	IEC 61300-2-18

SC Connector PC and APC - Single mode

OPTICAL PERFORMANCE*	LOW LOSS PREMIUM	STANDARD	CONFORMANCE
IL MAX/Master (Acceptance)	0.15dB	0.25dB	IEC 61300-3-4
IL MAX/Random (97%)	0.30dB	0.40dB	IEC 61300-3-34
Ave/Master	0.12dB	0.18dB	IEC 61300-3-4
Ave/Random	0.12dB	0.18dB	IEC 61300-3-34
Return	55/65dB	55/65dB	IEC 61300-3-6

SC Connector PC - Multimode

OPTICAL PERFORMANCE*	LOW LOSS PREMIUM	STANDARD	CONFORMANCE
IL MAX/Master (Acceptance)	0.15dB	0.30dB	IEC 61300-3-4
IL MAX/Random (97%)	0.25dB	0.40dB	IEC 61300-3-34
Ave/Master	0.08dB	0.15dB	IEC 61300-3-4
Ave/Random	0.10dB	0.20dB	IEC 61300-3-34

* Achievable with AFL Hyperscale process and specified optical fiber

ORDERING INFORMATION

Single mode		LOW LOSS PREMIUM		STANDARD	
PC	Simplex	900μm	SCSM9SMPX-P	SCSM9SMPX	
		2mm	SCSM2SMPX-P	SCSM2SMPX	
		3mm	SCSM3SMPX-P	SCSM3SMPX	
	Duplex	2mm	SCSM2DPX-P	SCSM2DPX	
		3mm	SCSM3DPX-P	SCSM3DPX	
APC	Simplex	900μm	SCAPC.9MM-P	SCAPC.9MM	
		2mm	SCAPC2MM-P	SCAPC2MM	
		3mm	SCAPC3MM-P	SCAPC3MM	
	Duplex	2mm	SCAPC2DPX-P	SCAPC2DPX	
		3mm	SCAPC3DPX-P	SCAPC3DPX	
Multimode		LOW LOSS PREMIUM		STANDARD	
PC	Simplex	900μm	SCMM9SMPX-P	SCMM9SMPX	
		2mm	SCMM2SMPX-P	SCMM2SMPX	
		3mm	SCMM3SMPX-P	SCMM3SMPX	
	Duplex	2mm	SCMM2DPX-P	SCMM2DPX	
		3mm	SCMM3DPX-P	SCMM3DPX	



SCAN QR FOR PRODUCT PAGE

FURTHER INFORMATION

- For additional information please contact your sales representative
- To view the product 360 visit the product page (Scan the QR code or visit the link below)
- Downloaded from <https://www.aflhyperscale.com/product/sc-connector>
- AFL Hyperscale reserves the right to make changes in this datasheet at any time without notice
- Information in this document is correct as of October 26, 2018

Europe

+44 (0) 1908 441 144
emeasales@aflhyperscale.com
© AFL Hyperscale 2019

Americas

+1 866 814 8615
usasales@aflhyperscale.com

Middle East & Africa

+971 4 404 9606
mesales@aflhyperscale.com

India

+91 80 46874687
indiasales@aflhyperscale.com

Asia Pacific

+86 755 2561 3694
apacsales@aflhyperscale.com