



Overview

| | |
|----------------------|---|
| Model Name | APC Back-UPS 1100VA, 230V, AVR, Universal and IEC Sockets |
| Includes | User Manual , Warranty card |
| Standard Lead Time | Usually in Stock |
| Product Distribution | Bangladesh , Bolivia , Cambodia , Chile , Indonesia , Malaysia , Myanmar , Nepal , Netherlands Antilles , Paraguay , Peru , Philippines , Singapore , Thailand , Uruguay , Viet Nam |

Output

| | |
|----------------------------------|--|
| Output Power Capacity | 550 Watts / 1100 VA |
| Max Configurable Power (Watts) | 550 Watts / 1100 VA |
| Nominal Output Voltage | 230V |
| Output Frequency (sync to mains) | 50/60 Hz +/-1 Hz |
| Output Frequency (sync to mains) | Line Interactive |
| Waveform Type | Stepped approximation to a sinewave |
| Output Connections | (2) IEC 320 C13 (Battery Backup) , (4) Universal Receptacle (Battery Backup) |

Input

| | |
|---|----------------------------------|
| Nominal Input Voltage | 230V |
| Input Frequency | 50/60 Hz +/- 3 Hz (auto sensing) |
| Input Connections | IEC-320 C14 , NEMA 5-15P |
| Cord Length | 1.22 meters |
| Input voltage range for main operations | 150 - 280 V |
| Maximum Input Current | 10 A |
| Input Breaker Capacity | 10 A |
| Type of Input Protection Required | 3-pole breaker |

Batteries & Runtime

| | |
|--------------------------|--|
| Battery Type | Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof |
| Included Battery Modules | 1 |
| Typical recharge time | 6 hour(s) |
| Replacement Battery | RBC17 |

Communications & Management

| | |
|---------------|--|
| Control panel | LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators |
| Audible Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

Surge Protection and Filtering

| | |
|---------------------|------------|
| Surge energy rating | 273 Joules |
|---------------------|------------|

Physical

| | |
|-----------------|----------|
| Maximum Height | 215.0 mm |
| Maximum Width | 130.0 mm |
| Maximum Depth | 336.0 mm |
| Net Weight | 9.2 kg |
| Shipping Weight | 10.6 kg |
| Shipping Height | 295.0 mm |
| Shipping Width | 245.0 mm |
| Shipping Depth | 440.0 mm |
| Color | Black |

Environmental

| | |
|---|---------------|
| Operating Environment | 0 - 40 °C |
| Operating Relative Humidity | 0 - 95 % |
| Operating Elevation | 0-3000 meters |
| Storage Temperature | -15 - 40 °C |
| Storage Relative Humidity | 0 - 95 % |
| Storage Elevation | 0-9000 meters |
| Audible noise at 1 meter from surface of unit | 45.000 dB |

Conformance

| | |
|-------------------|---------------------------|
| Approvals | CE , WEEE |
| Standard warranty | 2 years repair or replace |

Sustainable Offer Status

| | |
|-------|--------------------------|
| RoHS | Compliant |
| REACH | REACH: Contains No SVHCs |